



TECHNICAL DATASHEET DECARBONIZER & GASKET REMOVER

Ctra. Urnieta s/n
20140 Andoain
SPAIN
www.krafft.es
+34 943 410 400

PRODUCT DESCRIPTION

Universal decarbonizer to remove residues of soot in engine injectors.

The product is also designed to remove silicone gaskets in 30 minutes together traditional in 10-15 minutes.

BENEFITS AS DECARBONIZER

- Help disassembly of blocked nozzles, diluting solidified waste cinder preventing removal of the injector.
- When liquid penetrates more easily.
- Softens quickly and efficiently any kind of cinder accumulated in parts.

BENEFITS AS SEAL REMOVER

- Designed to assist in removal of cured chemical gaskets by softening the gasket material.
- Eliminate excessive scraping
- Especially suitable for removing parts together in aluminum or other soft metal surfaces where excessive scraping could easily damage the surface.

APPLICATIONS

- All kinds of diesel and gasoline engines.
- Injectors.
- Silicone packing and / or elastomers.

INSTRUCTIONS

AS DECARBONIZER

1. Shake well before using.
2. Apply directly to the area to be treated with short pulses.
3. If necessary, use the supplied nozzle.
4. Allow product to penetrate for 10-15 minutes.
5. Remove the injector.
6. Repeat if necessary.

AS GASKET REMOVER

1. Protect conveniently spray painted surfaces as product attacks the paint.
2. For best results, hold the container upright, at a distance of 20 to 30 cm from the seal area or surface and spray on the board or surface, a thick layer.
3. Leave for 10 to 15 minutes to soften the gasket. If silicone gaskets, leave take 30 minutes.
4. Remove the gasket with a soft scraper and clean the surface
5. Repeat if necessary.

ORDERING INFORMATION

Item no.	Content
35671	1 aerosol 500 ml

STORAGE

The products in sealed containers should be stored in a cool, dry place at a temperature of between 8 ° and 28 ° C.

NOTE

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. **Permatex, Inc. specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Permatex, inc. products and disclaims any liability for consequential or incidental damages of any kind, including lost profits.**