



## Gorilla® Heavy Duty Mounting Tape

**Product Description:** Gorilla Heavy Duty Mounting Tape provides a quick and convenient solution to mount and repair where traditional fasteners can't. This industrial strength tape conforms to smooth and rough surfaces, delivering an instant, crystal clear and weatherproof bond. Permanently bonds metal, wood, glass, brick, ceramic, stone and most plastics.

**Product Construction:** Transparent acrylic foam and adhesive, Clear removable liner

**Standard Size:** 60 inches long x 1-inch wide

### Physical Properties:

Property	Standard	Metric	Test Method
Thickness	39 mils	0.99 mm	N/A
Initial Tack	10 lbf / in <sup>2</sup>	44 N / 6.5 cm <sup>2</sup>	PSTC 16
Adhesion to Steel, 90 deg, 72h	14 lbf / in	62 N / 25 mm	PSTC 101
Static Shear, 1" x 1", 1000g, SS	>10,000 minutes	>10,000 minutes	PSTC 107
Elongation	300%	300%	PSTC 31
Temperature Range - Application	Above 50°F	Above 10°C	N/A
	Best At Room Temperature		
Temperature Range - In Service	up to 194°F (long term) up to 302°F (short term)	up to 90°C (long term) up to 150°C (short term)	N/A

Note: The technical information and data found in this data sheet is intended only as representative and should not be used for specification purposes. The information is given in good faith, with tests conducted by Quality Assurance and Technical Service Departments. Bond strength and cure times are dependent on a number of factors including moisture content and temperature during assembly and cure, bonding material and test method. Users should determine the suitability of the product for their own purposes by their own tests.